

SAFE OPERATING PROCEDURE FOR PROPANE MEMORIAL SPORTS CENTRE

- STORE ALL GAS CYLINDERS OUTSIDE IN THE LOCKED CAGE
- STORE FULL CYLINDERS IN THE UPRIGHT POSITION SO THAT LIQUID IS NOT IN CONTACT WITH THE RELIEF VALVE
- STORE EMPTY CYLINDERS COLLAR DOWN
- PUT ON PERSONAL PROTECTIVE EQUIPMENT WHEN EXCHANGING CYLINDERS
FACEMASK NEOPRENE GLOVES LONG SLEEVE SHIRT
- NEVER EXCHANGE CYLINDERS WITH THE ENGINE RUNNING
- CLOSE SUPPLY VALVE ON EMPTY CYLINDER
- LOOSEN AND REMOVE COUPLING
- UNDO RETAINING STRAP
- REMOVE EMPTY CYLINDER
- CHECK DATE STAMPS ON FULL CYLINDER AND INSPECT FOR DENTS CRACKS
GOUGES ETC.
- MAKE SURE CYLINDER HAS A WHIMIS LABEL
- INSTALL FULL CYLINDER MAKING SURE THAT LOCKING PIN IS ENGAGED IN
COLLAR
- FASTEN RETAINING STRAP
- MAKE SURE RUBBER GASKET IS IN PLACE
- CONNECT AND TIGHTEN COUPLING
- OPEN SUPPLY VALVE FULLY
- SOAP TEST CONNECTIONS FOR LEAKS